

TECHNICAL DATA SHEET

Manufacturer/ Supplier: KBM Sp. z o.o.
Address: 97-400 Bełchatów, ul. Czyżewskiego 31A
Telephone: + 48 44 633 61 26
Fax: + 48 44 633 79 42
E-mail: chemia@kbm.com.pl

PRODUCT: **WALLFIX BORDER ADHESIVE**

DESCRIPTION: Ready to use paste for borders and for repairing damaged parts of wallpapers. Wallfix Border Adhesive provides professional bonding. It is characterized by high adhesion force, high efficiency and moisture resistance.

PROPERTIES:

- very good initial adhesion (high strength of adhesion)
- easy to use
- the possibility of applying by roller and brush

Technical Data

Physical State:	paste
Form/color:	milky - white
Solubility in Water:	indefinite
Odour:	characteristic
Specific gravity:	1,09 +/- 0,05 g/m ³
Viscosity @ 20°C (mPas)	60 000 +/- 5000
pH	6,0 +/- 0,5

APPLICATION:	backed wallpapers. wallpapering. Stir well before applying to alignment the consistency. For heavy wallpaper it is not necessary to dilute the adhesive. Apply directly on the wall by roller or paintbrush, remove excess of the adhesive with a damp cloth or sponge.
SURFACE PREPARATION:	Surface should be dry, clean and free from old paint remains and grease. We recommend to use Masterline Sugar Soap which is especially designed to clean surfaces from dust and grease. Wall defects (scratches, holes) must be repaired. Old strips removed by Wallfix Wallpaper Stripper Concentrate. Cleaned, particularly absorbent surface, we recommend prime by Multi Ground, non-absorbent surface we recommend prime by Wallfix Primer Sealer Concentrate.
PACKAGING:	250g, 500g containers
STORAGE:	Store between 5 - 35°C, avoid from freezing.
PERFORMANCE:	250g /1,5 m ² 500g / 3,0 m ² – depends on the width of the strip.
EXPIRY DATE:	Expiration date located on the wrapping.
FIRST AID:	
Inhalation:	in normal conditions the product is not hazardous.
Skin Contact:	after work wash hands with warm water.
Eye Contact:	wash eyes with clean water; get medical attention if any discomfort continues.
Ingestion:	rinse mouth with plenty of water; get medical attention if any discomfort continues.
Fire:	non flammable.

RECOMMENDATION:

This data sheet defines the scope of the material and the method of works, but it can not replace the professional user preparation. What is more, work should be done in accordance with the construction and safety regulations.

The manufacturer guarantees the quality of the product, however, has no influence on the conditions and the way of its use. In case of any doubts, run your own tests.

The information given in the card is based on our current knowledge and experience.

The product should be used in accordance with applicable regulations and safety precautions.

The provided information cannot be applicable for mixtures of the product with other substances.

The applicability of the provided information and the usage of the product are not controlled by its producer and thus it is the user's responsibility to keep the safety conditions.