

TECHNICAL DATA SHEET

Manufacturer/ Supplier: KBM Sp. z o.o.
Address: 97-400 Bełchatów, ul. Czyżewskiego 31A
Telephone: + 48 44 633 61 26
Fax: + 48 44 633 79 42
E-mail: chemia@kbm.com.pl

PRODUCT: **WALLFIX PRIMER SEALER
CONCENTRATE**

DESCRIPTION: Dedicated for priming all types of surfaces: absorbent and porous such as walls, drywalls, ceilings, brick, stones, as well as non-absorbent surfaces, such as glass, metal, plastic, ect. It gives surface a smooth and sealed coat, which enhances adhesion, reduces the absorption, facilitates wallcoverings positioning and improves the coverage of paint. It is characterized by high adhesion force, high efficiency and moisture resistance

PROPERTIES:

- very good initial adhesion (high strength of adhesion)
- easy to use
- the possibility of applying by roller and brush

Technical Data

-	
Physical State:	paste
Form/color:	creamy - white
Odour:	characteristic
Specific gravity:	1,1 +/- 0,05 g/m ³
Viscosity @ 20°C (mPas)	13 000 +/- 5000
pH	6,0 +/- 0,5

APPLICATION:	backed wallpapers. wallpapering. For all buildings surfaces. Stabilizes the process of absorption, improves the adhesion of glue or paint coatings. Especially recommended before applying heavy wallpaper adhesives WALLFIX CONTRACT READY TO USE.
PREPARATION:	Primer diluted in a ratio of 1:3 - a typical surfaces; 1:1 - absorbent surfaces, such as fresh plaster, gypsum board panels. To the surface of a very low absorption such as glass, metal, plastic use without dilution. Apply on the surface a uniform layer with a brush or roller. After drying leaves a matt surface.
PACKAGING:	2,5kg – tightly closed bucket.
STORAGE:	Store between 5 - 35°C, avoid from freezing.
PERFORMANCE:	Up to 48 m ² / 1 liter
EXPIRY DATE:	12 months from the production date.
FIRST AID:	
Inhalation:	in normal conditions the product is not hazardous.
Skin Contact:	after work wash hands with warm water.
Eye Contact:	wash eyes with clean water; get medical attention if any discomfort continues.
Ingestion:	rinse mouth with plenty of water; get medical attention if any discomfort continues.
Fire:	non flammable.

RECOMMENDATION:

This data sheet defines the scope of the material and the method of works, but it can not replace the professional user preparation. What is more, work should be done in accordance with the construction and safety regulations.

The manufacturer guarantees the quality of the product, however, has no influence on the conditions and the way of its use. In case of any doubts, run your own tests.

The information given in the card is based on our current knowledge and experience.

The product should be used in accordance with applicable regulations and safety precautions.

The provided information cannot be applicable for mixtures of the product with other substances.

The applicability of the provided information and the usage of the product are not controlled by its producer and thus it is the user's responsibility to keep the safety conditions.