

## TECHNICAL DATA SHEET

---

**Manufacturer/ Supplier:** KBM Sp. z o.o.  
**Address:** 97-400 Bełchatów, ul. Czyżewskiego 31A  
**Telephone:** + 48 44 633 61 26  
**Fax:** + 48 44 633 79 42  
**E-mail:** chemia@kbm.com.pl

---

**PRODUCT:** **WALLFIX SPECIAL ADHESIVE  
PREMIUM LINE**

---

**DESCRIPTION:** Dedicated for light vinyl, vinyl foam, textured, paper and raufaser wallpapers. An adhesive based on methylcellulose polyvinyl acetate dispersion, contains fungicides.

### PROPERTIES:

- very good initial adhesion (high strength of adhesion)
- easy to use
- easy to fit design
- the possibility of applying a paint roller and brush
- ready to use after 15 minutes after mixing
- appearance of solution: white - transparent

### Technical Data

<b>Physical State:</b>	powder
<b>Form/color:</b>	creamy
<b>Odour:</b>	neutral
<b>Solubility in Water</b>	soluble in cold and lukewarm water
<b>Viscosity @ 23°C (mPas)</b>	10 000 – 30 000
<b>pH</b>	9,0 – 10,0

**APPLICATION:** For paper, vinyl, textured and rauhfasa wallpapers.

**USAGE INSTRUCTIONS:**

<b>WALLPAPER TYPE</b>	<b>QUANTITY</b>	<b>EFFICIENCY</b>
paper wallpapers	4.5	4-5 rolls; 35 m <sup>2</sup>
vinyl, textured	4	6 rolls; 30-35 m <sup>2</sup>
rauhfaser	4	3 rolls; 30-35 m <sup>2</sup>
sizing	8	60-80 m <sup>2</sup>

**SURFACE PREPARATION:** Surface should be dry, clean and free from old paint remains and grease. We recommend to use Masterline Sugar Soap which is especially designed to clean surfaces from dust and grease. Wall defects (scratches, holes) must be repaired. Old wallpaper removed by using Wallfix Wallpaper Stripper Concentrate. Cleaned, particularly absorbent surface, we recommend prime by Multi Ground or SPECIAL glue dissolved in water as recommended by the adhesive manufacturer.

**ADHESIVE PREPARATION:** Sprinkle the content of the box into cold water stirring briskly for 30 seconds. Stir again after approx. 3 minutes. Leave for 15 minutes. Stir well again before applying.

**PACKAGING:** 200g boxes; foil / cardboard packaging

**STORAGE:** Store between 5 - 25°C in a dry place.

**EXPIRY DATE:** 5 years from the production date.

**FIRST AID:**

**Inhalation:** in normal conditions the product is not hazardous.

**Skin Contact:** after work wash hands with warm water.

**Eye Contact:** wash eyes with clean water; get medical attention if any discomfort continues.

**Ingestion:** rinse mouth with plenty of water; get medical attention if any discomfort continues.

**Fire:** non flammable.

### **WALLPAPERING:**

Mixed adhesive Wallfix SPECIAL and apply evenly on the wallpaper.

Continue to follow the instructions of the manufacturer of wallpaper.

In the case of patterned wallpaper pay attention to the direction and pattern matching.

Wallpapering is best to start from the door or window openings, wallpaper expand downward toward the floor, cut and press roller with the soft rubber to get rid of air bubbles. Adhesive residue should be immediately washed off with a damp sponge and clean water.

### **RECOMMENDATION:**

This data sheet defines the scope of the material and the method of works, but it can not replace the professional user preparation. What is more, work should be done in accordance with the construction and safety regulations.

The manufacturer guarantees the quality of the product, however, has no influence on the conditions and the way of its use. In case of any doubts, run your own tests.

*The information given in the card is based on our current knowledge and experience.*

*The product should be used in accordance with applicable regulations and safety precautions.*

*The provided information cannot be applicable for mixtures of the product with other substances.*

*The applicability of the provided information and the usage of the product are not controlled by its producer and thus it is the user's responsibility to keep the safety conditions.*