



WALLFIX[®]
EXCELLENT ADHESIVE. TESTED.



TECHNICAL DATA SHEET

Manufacturer/Supplier: KBM Sp. z o.o.
Address: 97-400 Bełchatów, ul. Czyżewskiego 31A
Telephone: + 48 44 633 61 26
Fax: + 48 44 633 79 42
E-mail: chemia@kmb.com.pl

PRODUCT: WALLFIX READY TO USE CONTRACT MEDIUM

DESCRIPTION: Dedicated for non-woven vinyl and textile wallcoverings with a weight of 280 - 450 g/m². WALLFIX CONTRACT MEDIUM provides professional wallpaper adhesion, which powder adhesives can not guarantee. Has high efficiency and moisture resistance.

PROPERTIES:

- very good initial adhesion (high strength of adhesion)
- easy to use
- easy to fit design
- the possibility of applying a paint roller and brush

Technical Data

Physical State:	paste
Form/color:	milky white
Odour:	charakteristic
Solubility in Water	indefinite
Viscosity @ 30°C (mPas)	40 000 – 120 000 mPas
Specific Gravity	0,95- 1,17 g/cm ³
pH	6,0 – 7,5



WALLFIX[®]
EXCELLENT ADHESIVE. TESTED.



- APPLICATION:** For hanging non-woven vinyl and textile wallcoverings.
- SURFACE PREPARATION:** Surface should be dry, clean and free from old paint remains and grease. We recommend to use Masterline Sugar Soap which is especially designed to clean surfaces from dust and grease. Wall defects (scratches, holes) must be repaired. Old wallpaper removed by using Wallfix Wallpaper Stripper Concentrate. Cleaned, particularly absorbent surface, we recommend prime by Multi Ground, non-absorbent surface we recommend prime by Wallfix Primer Sealer Concentrate.
- USAGE INSTRUCTIONS:** After opening the container, the adhesive contents should be stirred well; apply the adhesive directly on the surface using a paint roller or paintbrush; excess of the adhesive should be removed with a cloth or sponge.
- EFFICIENCY:** 1kg of adhesive for 5 – 6 m²
- PACKING:** Plastic tightly closed buckets of capacity:
2,5 kg, 5 kg, 10 kg
- STORAGE:** Store between +5⁰ – 30⁰C, prevent from freezing.
- EXPIRY DATE:** 24 months from the production date.
- FIRST AID:**
- Inhalation:** in normal conditions the product is not hazardous.
- Skin Contact:** after work wash hands with warm water.
- Eye Contact:** wash eyes with clean water; get medical attention if any discomfort continues.
- Ingestion:** rinse mouth with plenty of water; get medical attention if any discomfort continues.
- Fire:** non flammable



WALLFIX[®]
EXCELLENT ADHESIVE. TESTED.



RECOMMENDATION:

This data sheet defines the scope of the material and the method of works, but it can not replace the professional user preparation. What is more, work should be done in accordance with the construction and safety regulations.

The manufacturer guarantees the quality of the product, however, has no influence on the conditions and the way of its use. In case of any doubts, run your own tests.

Information given in this sheet is based on our current knowledge and experience.

The product should be used in accordance with the currently valid regulations and good occupational hygiene practice. The presented information does not apply to mixtures of the product with other substances.

Use of the above given data, as well as the use of the product itself lie beyond the producer's control, thus setting rules of safe usage is the obligation of the user.